

**FAX**

**RECEIVED  
CENTRAL FAX CENTER**

**MAR 07 2005**

**From: Lloyd H. Woodward  
Serial No. 666,009**

**To: Hoang Nguyen**

**Dear Sir,**

**Please accept the following pages as  
replacement for the application number  
20050001774. I have attempted to follow the  
example, which you sent to me.**

**Best,**

**Lloyd H. Woodward, Sr.**

**Pages including this page - 11**

*PS. - this includes the abstract on a  
single page.*

*Thank You*

*LH W*

**Lloyd H. Woodward**  
**Serial number: 666,009**

### **Abstract**

A flexible multi-layered metallic tape for deflecting and blocking the RF radiation emitted by various antennas, particularly those used on cellular telephones, satellite telephones or military field radio-phones. Shaping of device around antenna causes multiple effects, including protecting the human user from harmful radiation, for military applications makes RF hard to DF and causes minor amplification of received signals by concentrating them on to antenna. The outer most part of the deflector shield should be made of a solid lead or gold tape that is six thousandths thick and 1/2" wide wherein a 1" length would weigh 1/4 gram. The outer most part would have an insulating flexible adhesive for cladding it to the next inner part. The first inner part of the shield should be made of solid copper foil. Best results coming from a foil that is at least three thousandths thick. Aside from having the outer most part cladded in parallel to it, it would have an insulating flexible adhesive for cladding it to the next inner part. The second inner part layer should be formed from 80 mesh 100% copper metal fabric; as shown in the drawing Figure 3 - Part 3. Aside from having the first inner part cladded in parallel to it, it would have an insulating flexible adhesive for attaching the shield to the mobile telephone, covered by a non-stick peel-off paper.

RECEIVED  
CENTRAL FAX CENTER

MAR 07 2005

United States Patent Application  
Kind Code  
*Woodward, Lloyd Harold*20050001774  
A1  
January 6, 2005**Flexible multi-cladded metallic tape for forming parabolic shaped magnetic field and energy deflecting devices**Inventors *Woodward, Lloyd Harold; (Dunn Loring, VA)*Correspo     *Lloyd H. Woodward*  
ndence       8005 Matt Court  
Name         Dunn Loring  
and           VA  
              22027-1001  
Address:      USSerial  
No.:        **666009**Series  
Code:      **10**Filed:      **September 21, 2003**

U.S. Current Class:

343/702; 343/841

U.S. Class at Publication:

343/702; 343/841

Intern'l Class:

H01Q 001/24; H01Q 001/52

**Abstract**

A flexible multi-layered metallic tape for deflecting and blocking the RF radiation emitted by various antennas, particularly those used on cellular telephones, satellite telephones or military field radio-phones. Shaping of device around antenna causes multiple effects, including protecting the human user from harmful radiation, for military applications makes RF hard to DF and causes minor amplification of received signals by concentrating them on to antenna. The outer most part of the deflector shield should be made of a solid lead or gold tape that is six thousandths thick and 1/2" wide wherein a 1" length would weigh 1/4 gram. The outer most part would have an insulating flexible adhesive for cladding it to the next inner part. The first inner part of the shield should be made of solid copper foil. Best results coming from a foil that is at least three thousandths thick. Aside from having the outer most part cladded in parallel to it, it would have an insulating flexible adhesive for cladding it to the next inner part. The second inner part layer should be formed from 80 mesh 100% copper metal fabric; as shown in the drawing Figure 3 - Part 3. Aside from having the first inner part cladded in parallel to it, it would have an insulating flexible adhesive for attaching the shield to the mobile telephone, covered by a non-stick peel-off paper.

**3 Claims, 4 Drawing Sheets**